

Attorney Docket No.: 03-0077.01

**AMENDMENTS TO THE CLAIMS**

1. (Currently Amended) An apparatus for the production of fatty acid alkyl ester comprising:
- a first tank for providing ~~containing~~ naturally occurring fatty acids;
  - a second tank for providing ~~containing~~ an alkaline solution;
  - a third tank for providing ~~containing~~ an alcohol;
  - a reaction chamber having an inlet for receiving an emulsion comprising a combination of said fatty acids, said alkaline solution and said alcohol, for the transesterification of said an emulsion in the presence of ultrasonic energy, and an outlet;
  - a natural gravity separatory coupled to said outlet, said separatory having a discharge comprising fatty acid alkyl ester; and
  - a centrifuge: for receiving said discharge and removing impurities therefrom.
2. (Original) The apparatus of Claim 1, wherein said naturally occurring fatty acids are animal fats.
3. (Original) The apparatus of Claim 1, wherein said naturally occurring fatty acids are vegetable oils.
4. (Original) The apparatus of Claim 1, wherein said alkaline solution is a concentrated form of one of the group comprising sodium hydroxide, potassium hydroxide, sodium methoxide,

Attorney Docket No.: 03-0077.01

potassium methoxide, ~~or~~ and other strong mineral alkaline solutions.

5. (Original) The apparatus of Claim 1, wherein said alcohol is one of the group comprising methanol, ethanol, propanol, and other monoalkyl alcohols.

6. (Cancelled)

7. (Cancelled)

8. (Currently Amended) The apparatus of Claim ~~7~~ 1, wherein said reaction chamber comprises:

~~a first inlet for the introduction of said emulsion;~~

~~a first outlet for the removal of a transesterified version of said emulsion;~~

a cooling jacket containing a pump fed flow of a cooling liquid for maintaining said reactor chamber at a defined temperature; and

~~a horn-~~ ultrasound generating means for propagating ultrasound radiation throughout said reaction chamber.

9. (Cancelled)

10. (Currently Amended) The apparatus of Claim ~~9~~ 8, wherein said ~~horn~~ ultrasenically

Attorney Docket No.: 03-0077.01

~~irradiates said emulsion~~ ultrasound generating means provides ultrasonic energy at specific frequencies of between generally about 20 kHz and generally about 50 KHz.

11. (Currently Amended) The apparatus of Claim 9 ~~8~~, wherein said ~~horn operates~~ ultrasound generating means provides ultrasonic energy at power densities of between generally about 18 Ws/ml and generally about 65 Ws/ml.

12. (Original) The apparatus of Claim 8, wherein said reaction chamber is maintained at an operating temperature of between generally about 70°C and generally about 80°C and an operating pressure of between generally about 1.0 and generally about 5.0 atmospheres.

13. (Currently Amended) The apparatus of Claim 7 ~~8~~, wherein said natural gravity separation operates to separate said transesterified emulsion into a glycerol solution and fatty acid alkyl ester.

14. (Original) The apparatus of Claim 13, wherein said fatty acid alkyl ester is introduced into said centrifuge for washing and drying, wherein said washing and drying involves the removal of traces of the catalyst, residual alcohol, and any remaining glycerol, soaps, and excess water.

15. (Original) The apparatus of Claim 14, wherein said washed and dried fatty acid alkyl ester is a pure biodiesel fuel requiring no additional processing to meet the ASTM standard for biodiesel.

Attorney Docket No.: 03-0077.01

16. (Withdrawn) A method for the production of fatty acid alkyl ester comprising the steps of:

- a) providing an emulsion of naturally occurring fatty acids, an alkaline solution and an alcohol;
- b) ultrasonically irradiating said emulsion to enhance the transesterification process;
- c) separating said transesterified emulsion into a glycerol solution and fatty acid alkyl ester using a natural gravity separatory; and
- d) washing and drying said fatty acid alkyl ester in a centrifuge to remove any remaining catalyst, alcohol, glycerol, soaps, and excess water.

17. (Withdrawn) The method of Claim 16, wherein said naturally occurring fatty acids are animal fats.

18. (Withdrawn) The method of Claim 16, wherein said naturally occurring fatty acids are vegetable oils.

19. (Withdrawn) The method of Claim 16, wherein said alkaline solution is a concentrated form of one of the group comprising sodium hydroxide, potassium hydroxide, sodium methoxide, potassium methoxide, or other strong mineral alkaline solutions.

20. (Withdrawn) The method of Claim 16, wherein said alcohol is one of the group

Attorney Docket No.: 03-0077.01

comprising methanol, ethanol, propanol, and other monoalkyl alcohols.

21. (Withdrawn) The method of Claim 16, wherein said transesterification of said emulsion occurs in a reaction chamber, and wherein said reaction chamber comprises a horn.

22. (Withdrawn) The method of Claim 21, wherein said horn ultrasonically irradiates said emulsion at frequencies between generally about 20 kHz to generally about 50 kHz.

23. (Withdrawn) The method of Claim 21, wherein said horn operates at power densities of between generally about 18 Ws/ml and generally about 65 Ws/ml.

24. (Withdrawn) The method of Claim 21, wherein said reaction chamber is maintained at a specific temperature of between generally about 70°C and generally about 80°C and an operating pressure of between generally about 1.0 and generally about 5.0 atmospheres.

25. (Withdrawn) A method for the production of fatty acid alkyl ester comprising the steps of:

- a) providing a naturally occurring fatty acid;
- b) providing an alkaline solution;
- c) providing an alcohol;
- d) emulsifying said naturally occurring fatty acid, said alkaline solution and said alcohol;

Attorney Docket No.: 03-0077.01

- e) transesterifying said emulsion at controlled temperatures and pressures;
- f) gravitationally separating said transesterified emulsion into a glycerine solution and fatty acid alkyl ester; and
- g) washing and drying said fatty acid alkyl ester in a centrifuge to remove any remaining catalyst, residual alcohol, glycerol, soaps, and excess water.

26. (Withdrawn) The method of Claim 25, wherein said naturally occurring fatty acids are animal fats.

27. (Withdrawn) The method of Claim 25, wherein said naturally occurring fatty acids are vegetable oils.

28. (Withdrawn) The method of Claim 25, wherein said alkaline solution is a concentrated form of one of the group comprising sodium hydroxide, potassium hydroxide, sodium methoxide, potassium methoxide, or other strong mineral alkaline solutions.

29. (Withdrawn) The method of Claim 25, wherein said alcohol is one of the group comprising methanol, ethanol, propanol, and other monoalkyl alcohols.

30. (Withdrawn) The method of Claim 25, wherein said transesterification of said emulsion occurs in a reaction chamber.

Attorney Docket No.: 03-0077.01

31. (Withdrawn) The method of Claim 30, wherein said transesterification occurs at a specific temperature of between generally about 70°C and generally about 80°C and an operating pressure of between generally about 1.0 and generally about 5.0 atmospheres.

32. (Withdrawn) The method of Claim 25, wherein said gravitationally separated fatty acid alkyl ester is washed in said centrifuge using a solution of warm, deionized water.

33. (Withdrawn) The apparatus of Claim 5, wherein excess alcohol loading of between generally about 0% to generally about 2.4% stoichiometric requirements per weight of said naturally occurring fatty acid is used in said production.

34. (Withdrawn) The method of Claim 20, wherein excess alcohol loading of between generally about 0% to generally about 2.4% stoichiometric requirements per weight of said naturally occurring fatty acid is used in said production.

35. (Withdrawn) The method of Claim 29, wherein excess alcohol loading of between generally about 0% to generally about 2.4% stoichiometric requirements per weight of said naturally occurring fatty acid is used in said production.

Attorney Docket No.: 03-0077.01

36. (New) The apparatus of Claim 1, wherein said third tank is configured to provide said alcohol at an excess loading level of generally about 0% to about 2.4% of stoichiometric requirements per weight of said naturally occurring fatty acid.
37. (New) The apparatus of Claim 36, wherein naturally occurring fatty acids are at least one of animal fats and vegetable fats.
38. (New) The apparatus of Claim 37, wherein said alkaline solution is a concentrated form of one of the group comprising sodium hydroxide, potassium hydroxide, sodium methoxide, potassium methoxide, and other strong mineral alkaline solutions.
39. (New) The apparatus of Claim 38, wherein said alcohol is one of the group comprising methanol, ethanol, propanol, and other monoalkyl alcohols.
40. (New) The apparatus of Claim 39, wherein said reaction chamber comprises:  
a cooling jacket containing a pump fed flow of a cooling liquid for maintaining said reactor chamber at an operating temperature of between generally about 70°C and generally about 80°C; and  
ultrasound generating means for propagating ultrasound radiation throughout said reaction chamber, and  
wherein said ultrasound generating means provides ultrasonic energy at frequencies of between



Attorney Docket No.: 03-0077.01

generally about 20 kHz and generally about 50 KHz, power densities of between generally about 18 Ws/ml and generally about 65 Ws/ml, and said reaction chamber is maintained at an operating pressure of between generally about 1.0 and generally about 5.0 atmospheres.

41. (New) A system for production of ASTM biodiesel fuel comprising:

an ultrasonic reaction chamber for transesterification of an emulsion in the presence of ultrasonic energy under pressure of between about 1.0 atmosphere and about 5.0 atmospheres and at temperature of between about 70°C to about 80°C, said emulsion comprising a mixture of naturally occurring fatty acids, an alkaline solution and an alcohol; and

a separatory for receiving said transesterified emulsion from said chamber and separating said transesterified emulsion into a fatty acid alkyl ester and a glycerine solution; and wherein said ultrasonic energy is at a frequency between about 20 kHz and about 50 KHz, and at a power density between about 18 Ws/ml and about 65 Ws/ml.

42. (New) The system of Claim 43, wherein said naturally occurring fatty acid is at least one of an animal fat and a vegetable fat.

Attorney Docket No.: 03-0077.01

43. (New) The system of Claim 43, wherein said alkaline solution is one of sodium hydroxide, potassium hydroxide, sodium methoxide, potassium methoxide, and other strong mineral alkaline solutions.

44. (New) The system of claim 43, wherein said alcohol is one of methanol, ethanol, propanol, and other monoalkyl alcohols.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**